

IN THE CLAIMS:

The listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended): A closure assembly of an opening of or in a building ~~or like structure~~, said closure assembly ~~including~~ comprising

at least two mutually pivoted panels (~~glazed or otherwise~~) mounted with the a mutual pivot axis at least substantially vertical and so as to be movable between:

(i) a closed condition whereby said at least two panels, at least substantially in mutual alignment, provide at least a partial closure of said opening in or substantially parallel to ~~the~~ a plane of ~~the~~ said opening, and

(ii) an opened condition whereby said at least two panels, mutually disaligned by having pivoted mutually towards each other, are substantially clear of ~~the~~ said plane of ~~the~~ said opening and where one of each, or all of said at least two panels, lie at an acute angle or parallel with respect to ~~the~~ said plane of ~~the~~ said opening,

~~wherein~~ one of said panels (~~the “proximate panel”~~) ~~is being~~ pivoted by an at least substantially vertical pivot axis substantially in ~~the~~ said plane of the opening at and/or adjacent a vertical periphery of said opening (~~“the proximal periphery”~~),

and ~~wherein~~ ~~the~~ a distal region of the other panel (~~the “distal panel”~~) ~~is being~~ supported by at least one supporting runner,

~~wherein the said~~ supporting runner running on a support track which, at least in part is skewed, ~~angled or angling, cranked or curved (hereafter "skewed")~~ with respect to ~~the said~~ plane of said opening, and ~~has the affect an effect~~ of spacing the ~~said~~ supporting runner out of ~~the said~~ plane of said opening at/or adjacent said proximal periphery, and

a locking pin being provided fixed relative to said building, said locking pin positioned to engage at said distal region of said other panel against an outwardly facing surface of said other panel when said panels are at and proximate to said closed condition to capture said other panel from moving outwardly.

Claim 2 (Currently Amended): ~~A- The~~ closure assembly as claimed in claim 1, wherein the proximate panel is pivoted by a ~~said~~ substantially vertical pivot axis fixed relative to said opening.

Claim 3 (Currently Amended): ~~A- The~~ closure assembly as claimed in claim 1, wherein said proximate panel is pivoted by a ~~said~~ substantially vertical pivot axis horizontally movable relative to and within the plane of the opening.

Claim 4 (Currently Amended): ~~A- The~~ closure assembly as claimed in claim 1, wherein said supporting runner includes a wheeled bogie engaged with the support track.

Claim 5 (Currently Amended): ~~A- The~~ closure assembly as claimed in claim 1, wherein said ~~support~~ supporting runner includes a vertical axis pivot to allow said wheeled bogie to pivot relative to said distal panel about a vertical axis.

Claim 6 (Currently Amended): ~~A-~~The closure assembly as claimed in claim 5, wherein said vertical axis of said pivot of said wheeled bogie is located at the mid thickness of said distal panel.

Claim 7 (Currently Amended): ~~A-~~The closure assembly as claimed in claim 1, wherein the support track is substantially rectilinear in form and is at an acute angle with respect to the plane of the opening.

Claim 8 (Currently Amended): ~~A-~~The closure assembly as claimed in claim 1, wherein the support track is at least in part rectilinear in form and said part is at an acute angle with respect to the plane of the opening.

Claim 9 (Currently Amended): ~~A-~~The closure assembly as claimed in claim 1, wherein the support track is rectilinear in form and parallel with the plane of the opening (~~preferably in the plane of the opening~~) save for that part thereof immediately proximal to the proximal periphery, where said support track is angled to the plane of said opening to step the supporting runner out of the plane of the opening.

Claim 10 (Currently Amended): ~~A-~~The closure assembly as claimed in claim 1, wherein the support track is curved.

Claim 11 (Currently Amended): ~~A-~~The closure assembly as claimed in claim 1, wherein the distal region of the ~~distal other~~ panel is supported by one supporting runner affixed at a vertical supported location either at the top or bottom (~~the~~ ~~“vertical supported location”~~) of the ~~distal other~~ panel.

Claim 12 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 11, wherein the other of said top or bottom to said vertical supported location is associated with a guiding runner tracked by a guiding track in the plane or parallel to the plane of the opening, ~~such~~ the guiding runner nevertheless allowing by ~~means of~~ an extensile association of the guiding runner with the ~~distal~~ other panel, movement for the ~~distal~~ other panel in following the support track defined locus allowing the distal region of the ~~distal~~ other panel to move as guided and pivoted with respect to the opening by the supporting runner guided by the support track.

Claim 13 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 11, wherein the other of said top or bottom to said vertical supported location is associated with a guiding runner tracked by a guiding track in the plane or parallel to the plane of the opening, ~~such~~ the guiding runner including an extensile arm pivotally attached to the distal panel, said extensile arm allowing the following of the support track defined locus required to allow the distal region of the ~~distal~~ other panel to move as constrained by said support track.

Claim 14 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 12, wherein the guiding runner includes an articulation ~~means~~ arm extending in a pivotal manner between the ~~distal~~ other panel, (at or towards the distal region,) said articulation ~~means~~ arm being further pivotally associated with said guiding track via a runner bogie located with and guided by the guiding track, thereby providing said extensile association.

Claim 15 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 14, wherein said articulation ~~means~~ arm is a rigid arm.

Claim 16 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 15, wherein said rigid arm extends perpendicular to said plane of said opening when said panels are in said open condition.

Claim 17 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 1, wherein the ~~support~~ supporting runner is provided at the top of the distal panel.

Claim 18 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 12, wherein the ~~guide~~ guiding runner is located at the bottom of the distal panel.

Claim 19 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 12, wherein the ~~guide~~ guiding runner is provided at the top of the ~~distal~~ other panel and the supporting runner is located at the bottom of the ~~distal~~ other panel.

Claim 20 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 1, wherein the distal region of the ~~distal~~ other panel is supported by a top and bottom located supporting runner, each supporting runner running in a respective said support track, disposed at the top and bottom of the opening.

Claim 21 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 1, wherein the ~~proximal~~ one panel is pivoted by a fixed vertical pivot axis at the ~~proximal~~ vertical periphery.

Claim 22 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 1, wherein said panels in an open position, lie substantially parallel to the plane of the opening.

Claims 23-26 (Cancelled)

Claim 27 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 1, wherein said supporting runner is a top runner affixed to a top or upper part of said ~~distal~~ other panel, and wherein said opening of or in said building includes a head framing, said support track is incorporated in a head assembly, said head assembly including

- a) a longitudinally extending foundation member to be fastened to the head framing of said opening with ~~its~~ a longitudinal direction of said foundation member extending parallel to the plane of said opening,
- b) a subassembly carrying the support track, fastened to said foundation member yet in a manner to allow the displacement of the said support track in a manner selected from at least one ~~or more of~~
 - (i) a linear manner to and from ~~the~~ a bottom of said opening, and
 - (ii) a manner to allow ~~the~~ tilt of said support track about a horizontal axis parallel to the plane of said opening.

Claim 28 (Cancelled)

Claim 29 (Currently Amended): ~~A~~ The closure assembly as claimed in claim ~~28~~ 27, wherein said foundation member is fixed to said side frame members.

Claim 30 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 28 27, wherein said subassembly is engaged to said foundation member by two arrays of vertically extending adjustment screws, a first array and a second array parallel to each other and to the plane of the opening;

- a) wherein ~~the differential adjustment of the said adjustment screws in one array relative to the said adjustment screws in the other array inducing induces~~ said tilt, and
- b) wherein corresponding adjustment of ~~the said adjustment screws in the both said first array and the said second array inducing the induces~~ displacement in said linear-displacement manner.

Claim 31 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 28 30, wherein said subassembly includes a pelmet with which said track is fastened and disposed therefrom in a manner to be exposed for engagement with the supporting runner.

Claim 32 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 31, wherein said pelmet extends outwardly from the plane of the opening sufficient to present from below thereof said support track and to allow ~~the~~ spacing of the supporting runner to assume the opened condition.

Claim 33 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 31 32, wherein said pelmet is an elongate, and substantially constant cross section extruded member.

Claim 34 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 33, wherein said pelmet includes trimming panels on each side of said support track spanning ~~the~~ any gap between said support track and ~~the~~ longitudinal edges of said pelmet.

Claim 35 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 30, wherein said first array of fastening screws is provided parallel to and on a first side of said plane of said opening and the second array is provided parallel to and on the other side of said plane of said opening.

Claim 36 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 30 35, wherein said screws of each array are equispaced.

Claim 37 (Cancelled)

Claim 38 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 25 64, wherein ~~a locking pin is provided fixed to said frame, said locking pin positioned to engage at distal region of said distal panel against an outwardly facing surface of said distal panel when said panels are at and proximate to its closed condition to capture~~ captures said distal region against a jam portion of said a frame to thereby prevent said distal region from moving outwardly.

Claim 39 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 25 38, wherein said ~~distal~~ other panel is supported at a top or bottom thereof by ~~a~~ said support runner and wherein at the other of said top or bottom the distal region of said ~~distal~~ other panel includes an outwardly facing surface ~~and wherein a locking~~

pin is provided fixed to said frame structure, said locking pin positioned to engage the outwardly facing surface of said distal panel when said panels are at and proximate to its closed condition to capture said distal region against a jam portion of said frame to thereby prevent said distal region from moving outwardly to be captured by said locking pin.

Claim 40 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 38 39, wherein said outwardly facing surface is a concealed ~~to~~ by the outside surface of said ~~distal~~ other panel.

Claim 41 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 1, wherein provided to the proximal periphery disposed region of said ~~proximal~~ one panel on the to be ~~distal~~ other panel facing side thereof when in the opened condition, is a first mutually attractive ~~means part~~, the ~~distal~~ other panel being provided at a corresponding location to ~~the~~ a location of said first mutually attractive ~~means part~~ on a proximal panel facing side thereof when in the opened condition, with a second mutually attractive ~~means part~~ to thereby allow the interaction of said mutually attractive ~~means parts~~ when said panels are in the opened condition to encourage said distal region of said ~~distal~~ other panel to remain engaged to the proximal periphery disposed region of said ~~proximal~~ other panel.

Claim 42 (Cancelled)

Claim 43 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 41, wherein said first and second mutually attractive ~~means parts~~ are both magnets.

Claim 44 (Currently Amended): ~~A~~ The closure assembly as claimed in claim 41-43, wherein said first and second mutually attractive ~~means-parts~~ are positioned towards the bottom of said panels.

Claim 45 (Withdrawn): A bifold door and/or window structure
at least a proximal panel and a distal panel
wherein

(a) the distal panel is provided at/or adjacent a lower distal region with a pivot on an extension of or from a lower track runner tracked in the plane of the opening to be closed by the door and/or window panels and,

(b) the distal panel is provided at or adjacent an upper distal region with a means to provide pivot tracking from a support track of the structure, said support track being skewed at least in part (whether straight, curved, kinked or otherwise)

and wherein together (a) and (b) have the affect of moving a thus defined common distal pivot axis of the distal panel out of the plane of the opening as the panels are opening thereby to allow the bifold door or window structure concertina back away from the opening with the proximal panel adjacent the building structure and the distal panel adjacent the proximal panel.

Claim 46 (Withdrawn): A guiding runner for supporting a lower distal region of distal panel of a bifold or multi-fold door and/or panel structure from a track, said guiding runner having an arrangement adapted to pivotally attach to said distal region of said distal panel,

a runner adapted to track said track, and

a link between the pivotal attachment and the runner, said link including two substantially parallel pivot axes whereby the link can range in its disposition from being aligned or substantially aligned in the plane of the tracking locus or extend outwardly therefrom to effectively space the pivot most proximal to the door and/or window panel from such plane of the tracking locus.

Claim 47 (Withdrawn): A guiding runner as claimed in claim 46 wherein such a guiding runner is substantially as hereinafter described with reference to any one or more of Figures 1B, 2, 3, 5, 6A-C, 11, 12.

Claim 48 (Withdrawn): Extrusions for framing an opening in a structure and for providing tracks for such a structure, wherein in subassembly or assembly they are adapted to form part of an assembly or structure of the closure assembly as claimed in claim 1.

Claim 49 (Withdrawn): In a building structure, a pair of tracks at an opening for a bifold or the like panel assembly, the lower track being in the plane of the opening and the upper track being skewed outwardly of the plane of the opening.

Claim 50 (Withdrawn): A bifold door and/or window structure comprising
at least a proximal panel and a distal panel
wherein

(a) the distal panel is provided at/or adjacent a lower or upper distal region with a pivot on an extension of or from a guiding track runner tracked in the plane of the opening to be closed by the door and/or window panels and,

(b) the distal panel is provided at or adjacent the other of said upper or lower distal region with a means to provide a pivot tracking from a support track of the door or window structure, said support track being skewed at least in part (whether straight, curved, kinked or otherwise)

and wherein together (a) and (b) have the affect of moving a thus defined common distal pivot axis of the distal panel out of the plane of the opening as the panels are opening thereby to allow the bifold door or window structure concertina back away from the opening with the proximal panel adjacent the building structure and the distal panel adjacent the proximal panel.

Claim 51 (Withdrawn): A guiding runner for supporting a lower or upper distal region of distal panel of a bifold or multi-fold door and/or panel structure from a track, said guiding runner having an arrangement adapted to pivotally attach to said distal region of said distal panel,

a runner adapted to track said track, and

a link between the pivotal attachment and the runner, said link including at least two substantially parallel pivot axes whereby the link can range in its disposition from being aligned or substantially aligned in or acute to the plane of the tracking locus when said bifold door is closed or extend outwardly therefrom to effectively space the pivot most proximal to the door and/or window panel from such plane of the tracking locus.

Claim 52 (Withdrawn): A guiding runner as claimed in claim 51 wherein such a guiding runner is substantially as hereinafter described with reference to any one or more of Figures 1B, 2, 3, 5, 6A-C, 11, 12.

Claim 53 (Withdrawn): Extrusions for framing an opening in a structure and for providing tracks for such a structure, wherein in subassembly or assembly they are adapted to form part of a closure assembly as claimed in claim 1.

Claim 54 (Withdrawn): In a building structure, a pair of tracks at an opening for a bifold or the like panel assembly, a first of said tracks positioned either as a lower or upper track and being in the plane of the opening and the second of said tracks being opposite to the first of said tracks being skewed outwardly of the plane of the opening.

Claim 55 (Withdrawn): In a building structure, a pair of tracks at an opening or a bifold or the like panel assembly, the upper track being in the plane of the opening and the lower track being skewed outwardly of the plane of the opening.

Claim 56 (Withdrawn): A pair of tracks at an opening or a bifold or the like panel assembly, the upper track being in the plane of the opening and the lower track being skewed outwardly of the plane of the opening, wherein said such track is of a kind capable of being used in a closure assembly as claimed in claim 1.

Claim 57 (Currently Amended): A building including a closure assembly to an opening of said building, said closure assembly ~~including~~ comprising

at least two mutually pivoted panels (~~glazed or otherwise~~) mounted with the a mutual pivot axis at least substantially vertical and so as to be movable between:

(i) a closed condition whereby said at least two panels, at least substantially in mutual alignment, provide at least a partial closure of said opening in or substantially parallel to ~~the~~ a plane of ~~the~~ said opening, and

(ii) an opened condition whereby said at least two panels, mutually disaligned by having pivoted mutually towards each other, are substantially clear of ~~the said plane of the said opening~~ and where one of each, or all of said at least two panels, lie at an acute angle or parallel with respect to ~~the said plane of the said opening~~,

~~wherein one of said panels (the “proximate panel”) is being pivoted by an at least substantially vertical pivot axis substantially in the said plane of the said opening at and/or adjacent a vertical periphery of said opening (“the proximal periphery”),~~

~~and wherein the a distal region of the other panel (the “distal panel”) is being supported by at least one supporting runner,~~

~~wherein the said supporting runner running on a support track which, at least in part is skewed, angled or angling, cranked or curved (hereafter “skewed”) with respect to the said plane of said opening, and has the affect an effect of spacing the said supporting runner out of the said plane of said opening at/or adjacent said proximal periphery, and~~

a locking pin being provided fixed relative to said building, said locking pin positioned to engage at said distal region of said other panel against an outwardly facing surface of said other panel when said panels are at and proximate to said closed condition to capture said other panel from moving outwardly.

Claim 58 (New): A closure assembly of an opening of or in a building, said closure assembly comprising

at least two mutually pivoted panels mounted with a mutual axis at least substantially vertical and so as to be movable between:

(i) a closed condition whereby said at least two panels, at least substantially in mutual alignment, provide at least a partial closure of said opening in or substantially parallel to a plane of said opening, and

(ii) an opened condition whereby said at least two panels, mutually disaligned by having pivoted mutually towards each other, are substantially clear of said plane of said opening and where one of each, or all of said at least two panels, lie at an acute angle or parallel with respect to said plane of said opening,

one of said panels being pivoted by an at least substantially vertical pivot axis substantially in said plane of the opening at and/or adjacent a vertical periphery of said opening,

and a distal region of the other panel being supported by at least one supporting runner,

said supporting runner, running on a support track which, at least in part is skewed with respect to said plane of said opening, and has an effect of spacing said supporting runner out of said plane of said opening at/or adjacent said proximal periphery,

said closure assembly being fully framed and a perimeter of said fully framed closure assembly being defined by a frame structure of a size to be received in said opening of or in said building, and

a locking pin and bump strip being provided fixed relative to said building, said locking pin positioned to engage at said distal region of said other panel against an outwardly facing surface of said other panel, and said bump strip positioned to engage an inwardly facing surface of said other panel when said panels are at and proximate to said closed condition, to capture at least part of said other panel between said locking pin and said bump strip and prevent said other panel from moving outwardly.

Claim 59 (New): The closure assembly as claimed in claim 58, wherein said frame structure is at least in part an assembly of extruded forms.

Claim 60 (New): The closure assembly as claimed in claim 59, wherein said frame structure includes

- a top frame extrusion,
- a bottom frame extrusion parallel to said top frame extrusion and to extend horizontally in use, and
- two side frame extrusions affixed to and extending between said top and bottom frame extrusions and parallel to each other and to in use extend vertically.

Claim 61 (New): The closure assembly as claimed in claim 60, wherein said supporting runner is a top runner affixed to a top or upper part of said other panel, wherein said top frame extrusion is a head assembly, said head assembly including

- a) a longitudinally extending foundation member to be fastened to said building and in a manner with a longitudinal direction of said foundation member parallel to said plane of said opening,
- b) a subassembly carrying said support track, fastened to said foundation member yet in a manner to allow displacement of said support track in a manner selected from at least one of
 - (i) a linear manner to and from said foundation member, and
 - (ii) a manner to allow tilt of said track about a horizontal axis parallel to said plane of said opening.

Claim 62 (New): The closure assembly as claimed in claim 61, wherein said foundation member is fixed to said side frame members.

Claim 63 (New): The closure assembly as claimed in claim 1, wherein said panels are glazed.

Claim 64 (New): The closure assembly as claimed in claim 9, wherein said support track is in said plane of said opening.